# General Care & Maintenance Luxury Vinyl Plank

#### GENERAL CARE AND MAINTENANCE

Proper care will help protect and maintain the appearance and performance of your DCM luxury vinyl flooring. A care program consists of key areas: 1) Preventive maintenance; 2) routine maintenance; 3) spot and spill removal.

Allow the recommended minimum of 24 hours before moving heavy objects. New floors should not be saturated or wet cleaned for 5 days after installation. Only damp mopping is recommended between installation and the 5-day period.

#### PREVENTIVE MAINTENANCE

- Always protect floors when moving heavy objects to prevent permanent scratches and tears. The use of plywood and heavy cardboard are examples of protective barriers.
- Use appropriate wide floor protectors under tables, chairs, and other heavy home furnishing to avoid permanent damage.
- Walk-off mats should be used at all entrances to absorb soil and moisture. If mats are placed directly on top of floor, use mats without latex or rubber backings..

### **ROUTINE MAINTENANCE**

- Daily removal of dirt and dust is important in the maintenance of your floor.
  Sweeping, dust mopping, vacuuming are recommendations to remove soil particles that can result in scratches and worn appearances. Do not use vacuums with rotating beater bars on hard surfaces.

## SPOT AND SPILL REMOVAL

- Absorb wet spills as quickly as possible by blotting with white paper or cloth towels.
  Rinse with water if necessary and blot dry.
- Dried spots should be removed by gentle agitation and rinsed with water. Blot dry.
- Do not use detergents or abrasive cleaners since these products can leave a dull residue.
- Use rubbing alcohol (isopropyl alcohol) with a clean white cloth for spots requiring a solvent type cleaner that water and cleaning agents cannont remove.